



A-750 Audiometric Mini-Booth

The A-750 Mini booth, designed to prioritise **everyday function & space optimization**, is engineered to allow flexibility in all environments:

- **For Hearing Health Professionals**
- **Industrial / Workplace Testing**
- **Speech audiometry** (through earphones)
- **Mobile test vans and medical centres**



Phone: 01664 568728

Email: sales@agsnoisecontrol.co.uk

All details correct as of May 2026

Dimensions & Weight

	W (mm)	D (mm)	H (mm)
Outside Dimensions	780	975	1885
Inside Dimensions	600	870	1690

Net Weight: 210kg

Shipping weight: 225kg

Fully equipped and assembled booth fits through any normal 830mm clear opening door (750mm without attached shelf).

Construction

Omnifit-AG1™ panels – exterior surfaces plain powder coated steel with interior surfaces perforated powder coated steel.

The booth can be assembled to accommodate left-handed or right-handed opening.

Door

One PortaQuita™ door provides a 606mm wide x 1686mm high clear opening.

Acoustic integrity is achieved by magnetic seals mounted on all 4 sides of the door frame.

Window

One double glazed unit comprising of two 6.4mm thick laminated safety glass fitted in anodized aluminium frames; clear view area 765mm high x 540mm wide.

Ventilation

Ceiling panel contains an integrated low-voltage silenced ventilation system.

Audiometric Jack Panel

Completely pre-wired, flush-mounted jack panel consists of six (6) 6mm 3 pole sockets (1/4" Jack) & two USB Type A connections.

Data

To comply with the ISO standard BS EN ISO 8253-1:2010 the appropriate permissible background/external noise level is no greater than 57dB (at 500Hz) with noise barrier headset (Audio cups).

Lighting

Maintenance free LED ceiling mounted recessed light, low voltage. Complete with exterior switch (optional extra).

UKCA compliant, low voltage lighting and ventilation, supplied via a 3 pin 230V mains power adapter (included).



Floor

Interior foam-backed carpet, colour blue. Exterior castors for manoeuvring & positioning.

Standard Finish

White polyester powder paint, RAL 9010 matt. Exterior and interior.

Installation

Booth is supplied flatpack or pre-assembled.

Standard delivery is kerbside. 'White glove delivery' service available where access is difficult for an assembled unit. On-site assembly installation is also an available service.

Site requirements:

- Customer to provide a finished floor which is within +/- 6mm of level in 3 non-cumulative metres
- 100mm minimum clearance height is required between exterior of testing booth and host facility walls/ceilings

Optional equipment

(Additional costs apply)

- (a) Anti-vibration mounts (replace castors)
- (b) Alternative panel colour
- (c) One-way perforated vision film applied to the bottom section of the window.
- (d) Externally mounted folding shelf for audiometer or equipment, 680mm wide x 450mm deep.
- (e) Fabric lined interior and vinyl flooring available
- (f) Internal seat, 4-legged, backed chair
- (g) Alternative wired jack panels

